ESCABOCABLE - MINOCABLE

ESCABOCABLE

Ideal for computer and telephone network installers

Both trolley and unwinder, it is ideal for on-site operations.

Foldable, it takes up very little space in a vehicle.

It does not damage anything in its vicinity.

The ESCABOCABLE can be **modulated** according to the diameter of the spools: it is delivered with 3 shafts Ø12 mm (effective length 490mm), with **5 adjustable posi-**

The max. diameter of spools is

- 300mm with the 3 shafts
- 400mm with 2 shafts only
- 900mm with 1 shaft only.

Spool max. load: 30kg. Total max. load: 60 kg. **Delivered empty.**



It can be optionally fitted with

- in case of wire coils:

up to 9 spools with straps \varnothing 300mm max. width 100mm (code E3300390)

- in case of cable coils:

up to 4 spools with straps \varnothing 400mm max. width 150mm (code E3300490)

Made of steel tube with epoxy powder coated finish, galvanised steel shafts.

2 wheels Ø 180mm

Dimensions

- bent: w 650 x D 300 x H 1150 mm - open: w 650 x D 850 x H 1040 mm

Width out-to-out: Spool 400: 210mm Spool 300: 160mm

Weight: 9kg



MINOCABLE

Our smallest coil holder

For use on sites (it can be easily hand carried), as well as in workshops and laboratories.

Code: E3500660

Suitable for spools

- Max. Ø **400mm**
- Min. Ø of central hole 12mm.

Shaft length available for the spools: 490mm

Delivered empty.

It may be equipped with

- in case of wire coils:

up to 3 spools with straps Ø 300mm max. width 100mm (code E3300390)

- in case of cable coils:

up to 2 spools with straps Ø 400mm max. width 150mm (code E3300490)

Made of steel tube with epoxy powder coated finish, galvanised steel shaft.

Dimensions w 550 x D 250 x H 275 mm Width **out-to-out** : Spool 400: 210mm Spool 300: 160mm

Weight: 2.7kg (net)



Enrouleurs - Dérouleurs - Métreuses - Protège-câbles

21 rue Sadi Carnot 94880 NOISEAU (France)

Tel: (33) 01 45 90 14 14 Fax: (33) 01 45 90 17 17 contact@cable-equipements.com











MAXI

