

Automatic Cable Reels THE UNMISSABLE



October 2022



New GREEN REEL range



GREEN REEL by Cable Equipements

Do the same gesture as at the gas station

To charge your electric car:

- 1 - Pull the cable, it unwinds
- 2 - Plug in, the car is charging
- 3 - Unplug, the cable rewinds itself
- 4 - Hit the road!



Faster and cleaner

User of an electric or plug-in hybrid car: you no longer have to painfully store a dirty and wet cable in your trunk



Safer and more durable

The cable no longer drags on the ground: it does not deteriorate and does not risk causing falls



For individuals

(private residential: individual or collective)



For professionals

(companies, communities, vehicle fleets, hotels, etc.)

2 types of automatic cable reels



You don't have a charging station

Single-phase

GREEN REEL 3.7
with integrated charging station



You have a charging station

Single-phase

maxi 7,4 kW

GREEN REEL 7.4

Three-phase

maxi 22 kW

GREEN REEL 22



Model	Maximum power	Length	Power supply	Type 2 socket	Code
GREEN REEL 3.7 station	3,7 kW	4 meters	Single-phase 16A	Output	ERVWB-T2
GREEN REEL 7.4	7,4 kW	10 meters	Single-phase 32A	Input and output	ERV07-S5-T2
GREEN REEL 22	22 kW		Three-phase 32A		ERV22-S5-T2

New EURO range

The professional quality at the best price



Made in
Europe



3 years
warranty



Certified CE
(by the manufacturer)
EN 61242 EN 60335-1
2014/35/UE 2006/42/CE 2011/65/UE



Availability
in 1 day

Plastique case - Swivelling bracket - Removable ratchet - Horizontal and vertical use

3G1,5² with plugs

P301



11 meters
3G1,5 mm² - H07RN-F

P421



22 meters
3G1,5 mm² - H07RN-F

Model	Total length	Cable type	IP	kW (20°C)		kW (20°C)		Thermal protector	Plug outgoing cable	Plug incoming cable	Incoming cable	Dimensions (mm)	Code
P301	11 m	H07RN-F	42	230V	1,2	230V	1,8	Yes	Female 2P+T	Male 2P+T	1,50 m	H290x1375xP165	ER03015-11R-P301
P421	22 m				1,1		1,8	No				H365x1485xP195	ER03015-22R-P421

3G2,5² with plugs

P302



10 meters
3G2,5 mm² - H07RN-F

P412



17 meters
3G2,5 mm² - H07RN-F

P422



20 meters
3G2,5 mm² - H07RN-F

Model	Total length	Cable type	IP	kW (20°C)		kW (20°C)		Thermal protector	Plug outgoing cable	Plug incoming cable	Incoming cable	Dimensions (mm)	Code
P302	10 m	H07RN-F	42	230V	1,9	230V	2,5	Yes	Female 2P+T	Male 2P + T	1,50 m	H290x1375xP165	ER03025-10R-P302
P412	17 m				2,0		3,0	No				H365x1485xP195	ER03025-17R-P412
P422	20 m												ER03025-20R-P422

Grounding

P106



7 meters
1x6 mm² - H05VV-F

P306



16 meters
1x6 mm² - H05VV-F

Model	Section (mm ²)	Total length	Cable type	Delivered	IP	Incoming cable	Dimensions	Code
P106	1x6	7 m	H05VV-F	with clips	42	1,50 m	H190x1220xP115	ER01060-07V-P106
P306		16 m					H290x1375xP165	ER01060-16V-P306

3G1,5² : the unmissable

P105



6 meters
3G1,5mm² - H05VV-F
Plastic case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

P506



10 meters
3G1,5mm² - H07RN-F
Plastic case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

P301



11 meters
3G1,5 mm² - H07RN-F
Plastic case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

**3 years
Warranty**

A315



15 meters
3G1,5mm² - H05VV-F
ALUMINIUM case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

**5 years
Warranty**

P315



15 meters
3G1,5mm² - H05VV-F
Plastic case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

P421



22 meters
3G1,5 mm² - H07RN-F
Plastic case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

**3 years
Warranty**

P803



22 meters
3G1,5mm² - H07RN-F
Plastic case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

Model	Total length	Cable type	IP	kW (20°C) 		kW (20°C) 		Thermal Protector	Plug outcoming cable	Plug incoming cable	Incoming cable	Dimensions (mm)	Art.	
P105	6 m	H05VV-F	42	230V	1,4	230V	1,9	Yes	Option	Option	-	H190xl220xP115	ER03015-06V-P105	
P506	10 m	H07RN-F			1,2		1,8		No	Option	Option	-	H290xl350xP160	ER03015-10R-P506
P301	11 m												Female 2P+T	Male 2P+T
A315	15 m	H05VV-F		1,2	1,8	Yes	Option	Option					-	H290xl375xP175
P315									H290xl375xP165	ER03015-15V-P315				
P421	22 m	H07RN-F		1,1		No	Female 2P+T	Male 2P+T	1,50 m	H365xl485xP195	ER03015-22R-P421			
P803							Option	Option	-	H380xl470xP205	ER03015-22R-P803			

3G2,5² : the unmissable

A325



8 meters
3G2,5mm² - H07RN-F
ALUMINIUM case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

5 years
Warranty

P325



10 meters
3G2,5mm² - H07RN-F
Plastic case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

P510



10 meters
3G2,5mm² - H05VV-F
Plastic case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

P302



10 meters
3G2,5 mm² - H07RN-F
Plastic case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

3 years
Warranty

P511



12 meters
3G2,5mm² - IGUS
Plastic case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

P805



12 meters
3G2,5mm² - H07RN-F
Plastic case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

P412



17 meters
3G2,5 mm² - H07RN-F
Plastic case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

3 years
Warranty

P806



19 meters
3G2,5mm² - H07RN-F
Plastic case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

P422



20 meters
3G2,5 mm² - H07RN-F
Plastic case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

3 years
Warranty

S503



20 meters
3G2,5mm² - H07RN-F
STEEL open case
Ratchet in option
Horizontal and vertical use
Options : data sheet STEEL 500

S8V02



31 meters
3G2,5mm² - H07RN-F
STEEL open case type 1
Ratchet removable
Horizontal and vertical use
Options : data sheet STEEL 800

S8H05



41 meters
3G2,5mm² - H07RN-F
STEEL open case type 1
Ratchet removable
Horizontal use
Options : data sheet STEEL 800

Model	Total length	Cable type	IP	kW (20°C) 		kW (20°C) 		Thermal Protector	Plug outcoming cable	Plug incoming cable	Incoming cable	Dimensions (mm)	Art.							
A325	8 m	H07RN-F	42	230V	1,9	2,5	No	Option	Option	-	H290x1375xP175	ER03025-08R-A325								
P325	10 m						H05VV-F					Yes	Option	Option	-	H290x1375xP165	ER03025-10R-P325			
P510		H07RN-F															Female 2P+T	Male 2P+T	1,50 m	H290x1350xP160
P302								Option	Option	-	H290x1375xP175									
P511	12 m				IGUS CF77	Option	Option					-	H290x1350xP160	ER03025-12P-P511						
P805		H380x1470xP205												ER03025-12R-P805						
P412														Female 2P+T	Male 2P+T	1,50 m	H365x1485xP195	ER03025-17R-P412		
P806	Option							Option	-	H380x1470xP205	ER03025-19R-P806									
P422			20 m	Female 2P+T		Male 2P+T	1,50 m				H365x1485xP195	ER03025-20R-P422								
S503		Option										Option	-					Ø360xP330	ER03025-20R-S503	
S8V02														31 m	65	230V	2,0		3,0	No
S8H05	41 m		ER03025-41R-S8H05																	

4G2,5² : the unmissable

P515



9 meters
4G2,5mm² - H05VV-F
Plastic case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

P811



15 meters
4G2,5mm² - H07RN-F
Plastic case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

P812



20 meters
4G2,5mm² - H05VV-F
Plastic case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

S8V04



31 meters
4G2,5mm² - H07RN-F
STEEL open case
Ratchet removable
Horizontal and vertical use
Options : data sheet STEEL 800

S8H07



41 meters
4G2,5mm² - H07RN-F
STEEL open case
Ratchet removable
Horizontal use
Options : data sheet STEEL 800

S8H09



55 meters
4G2,5mm² - H07RN-F
STEEL open case
Ratchet in option
Horizontal use
Options : data sheet STEEL 800

Model	Total lenght	Cable type	IP	kW (20°C) 		kW (20°C) 		Slipring capacity	Thermal Protector	Incoming cable	Dimensions (mm)	Art.
P515	9 m	H05VV-F	42	400V	2,0	400V	2,7	-	-	-	H290xI350xP160	ER04025-09V-P515
P811	15 m	H07RN-F					3,0				H380xI470xP205	ER04025-15R-P811
P812	20 m	H05VV-F					32 A					ER04025-20V-P812
S8V04	31 m	H07RN-F	65	400V	7,0	400V	10,0	32 A	-	2,5 m	Ø440xP365	ER04025-31R-S8V04
S8H07	41 m				6,0		8,5				ER04025-41R-S8H07	
S8H09	55 m				Ø550xP395		ER04025-55R-S8H09					

5G2,5² : the unmissable

P520



7 meters
5G2,5mm² - IGUS CF77
Plastic case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

P815



12 meters
5G2,5mm² - H07RN-F
Plastic case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

P816



17 meters
5G2,5mm² - H05VV-F
Plastic case
Swivelling bracket
Ratchet removable
Horizontal and vertical use

S8V28



22 meters
5G2,5mm² - H07RN-F
STEEL open case
Ratchet removable
Horizontal and vertical use
Options : data sheet STEEL 800

S8H33



31 meters
5G2,5mm² - H07RN-F
STEEL open case
Ratchet removable
Horizontal use
Options : data sheet STEEL 800

S8H35



55 meters
5G2,5mm² - H07RN-F
STEEL open case
Ratchet in option
Horizontal use
Options : data sheet STEEL 800

Model	Total length	Cable type	IP	kW (20°C)		kW (20°C)		Thermal Protector	Slipping capacity	Incoming cable	Dimensions (mm)	Art.
P520	7 m	IGUS CF77	42	400V	2,0	400V	2,7	10 A	-	-	H290xI350xP160	ER05025-07P-P520
P815	12 m	H07RN-F					3,0	-			H380xI470xP205	ER05025-12R-P815
P816	17 m	H05VV-F										ER05025-17V-P816
S8V28	22 m	H07RN-F	65	400V	7,0	400V	9,5	32 A	-	2,5 m	Ø440xP365	ER05025-22R-S8V28
S8H33	31 m										Ø550xP365	ER05025-31R-S8H33
S8H35	55 m				6,0		8,5				Ø550xP395	ER05025-55R-S8H35



P106



7 meters
1x6 mm² - H05VV-F
 Plastic case
 Swivelling bracket
 Ratchet removable
 Horizontal and vertical use

P306



16 meters
1x6 mm² - H05VV-F
 Plastic case
 Swivelling bracket
 Ratchet removable
 Horizontal and vertical use

P502



11 meters
1x16mm² - H05VV-F
 Plastic case
 Swivelling bracket
 Ratchet removable
 Horizontal and vertical use

P801



22 meters
1x16mm² - H05VV-F
 Plastic case
 Swivelling bracket
 Ratchet removable
 Horizontal and vertical use

S8H01



32 meters
1x16mm² - H05VV-F
 STEEL open case
 Ratchet removable
 Horizontal use
 Green/yellow cable
 Options : data sheet STEEL 800

S502



20 meters
1x25mm² - H05VV-F
 STEEL open case
 Ratchet in option
 Horizontal and vertical use
 Green/yellow cable
 Options : data sheet STEEL 500

S8H02



32 meters
1x25mm² - H05VV-F
 STEEL open case
 Ratchet removable
 Horizontal use
 Green/yellow cable
 Options : data sheet STEEL 800



Other models in the ATEX range



Clips



40 A
 Maxi 2,5 mm²
 ERP040N et ERP040R



150 A
 Maxi 16 mm²
 ERP150N et ERP150R



200 A isolated
 Maxi 16 mm²
 ERP200N et ERP200R



220 A
 Maxi 25 mm²
 ERP220N et ERP220R



400 A
 Maxi 25 mm²
 ERP400N et ERP400R

Model	Section (mm ²)	Total length	Cable type	Delivered	IP	Incoming cable	Dimensions (mm)	Art.
P106	1x6	7 m	H05VV-F	with clip	42	1,50 m	H190x1220xP115	ER01060-07V-P106
P306		16 m					H290x1375xP165	ER01060-16V-P306
P502		11 m				-	H290x1350xP160	ER01160-11V-P502
P801	1x16	22 m					H380x1470xP205	ER01160-22V-P801
S8H01		32 m			65	2,50 m	Ø440xP365	ER01160-32V-S8H01
S502	1x25	20 m				-	Ø360xP330	ER01250-20V-S502
S8H02		32 m				2,50 m	Ø440xP365	ER01250-32V-S8H02

Hose reels : the unmissable

Industrial quality - European manufacturing

For air and water.

3 years
Warranty



New



YP308KPU



YP310KPU



YP312KPU

Length	Interior hose Ø		ATEX	Hose type	Max pressure	End hose fitting	Dimensions	Weight	Model	Code
10 meters	8 mm	5/16"	No	Blue KPU	20 bar	1/4" M BSP	H290 x I380 x P160 mm	3,35 kg	YP308KPU	Y-10-5/16-20-YP308KPU
16 meters	10 mm	3/8"				3/8" M BSP	H380 x I490 x P210 mm	6,30 kg	YP310KPU	Y-16-3/8-20-YP310KPU
	12,5 mm	1/2"	Yes			1/2" M BSP	H460 x I565 x P235 mm	8,70 kg	YP312KPU	YATX-16-1/2-20-YP312KPU

Safety Barriers

Equipped with ribbon or chain.
8 meters or 20 meters.



Codes ERS...

Signal transmission

ATEX



Codes ERT...



Codes ERATX...

MAGIC REEL

Automatic extension:
the cable unwinds and winds up automatically.
3G2,5².

New



MAGIC REEL 10

Model	Length	Code
MAGIC REEL 10	10 m	ERU03025/10
MAGIC REEL 17	17 m	ERU03025/17

EV-REEL

Manual winder for your
charging cable.

New



Code EV-REEL

Battery charging



Codes ERB...

Reels with lamps



Codes ERL...

Other electric reels

PLT 100



Models P1...

PLT 500



Models P5...

PLT 600 - 600S



Models P6... and PS6...

PLT 800



Models P8...

ALU 700 - 700S ALU 700/65 - 700S/65



Models A7... and AS7...

STEEL 500



Models S5...

STEEL 800



Models S8...

STEEL 900



Models S9...

Other hose reels



Codes ERY...



Lamps



Codes BA... BF... BL...

Balancers



Codes EQ...

How to select the right reel ?

among our 500 references ?

On website www.cable-equipements.com
Use our **ONLINE CONFIGURATOR**

Conductors: Cable section (mm²): Cable length (meters): Cable type: Use: ☐ horizontale ☐ horizontale et verticale IP: Ratchet: Available: ☐ RESET SEARCH

P520 Family 5G2,5² AVAILABLE  5G2,5² 7 meters IGUS CF77 IP42 ou 43 Utilisation horizontale et verticale Cliquet supprimable Code : ER05025-07P-P520	P815 Family 5G2,5² AVAILABLE  5G2,5² 12 meters H07RN-F IP42 ou 43 Utilisation horizontale et verticale Cliquet supprimable Code : ER05025-12R-P815	P816 Family 5G2,5² AVAILABLE  5G2,5² 17 meters H05VV-F IP42 ou 43 Utilisation horizontale et verticale Cliquet supprimable Code : ER05025-17V-P816	S8V28 Family 5G2,5² AVAILABLE  5G2,5² 22 meters H07RN-F IP65 Utilisation horizontale et verticale Cliquet supprimable Code : ER05025-22R-S8V28
S8H33 Family 5G2,5² AVAILABLE  5G2,5² 31 meters H07RN-F IP65 Utilisation horizontale Cliquet supprimable Code : ER05025-31R-S8H33	S8H35 Family 5G2,5² AVAILABLE  5G2,5² 55 meters H07RN-F IP65 Utilisation horizontale Cliquet en option Code : ER05025-55R-S8H35	A729 Family ALU 700  5G2,5² 10 meters H07RN-F IP42 ou 43 Utilisation horizontale et verticale Cliquet supprimable Code : ER05025-10R-A729	A731 Family ALU 700  5G2,5² 12 meters H05VV-F IP42 ou 43 Utilisation horizontale et verticale Cliquet supprimable Code : ER05025-12V-A731

What our code means :

ER Spring drums
03 Numbers of conductors = 3
025 Section = 2,5 mm²
-
10 Length = 10 meters
V Cable type
 V = H05VV-F
 R = H07RN-F
 P = Polyuréthane
-
P510 Model name = P510

Send your enquiry With your exact need :

Numbers of conductors and cable section : Use : horizontal ☐ vertical ☐
 Length : Use : inside ☐ Outside ☐
 Quantity :
 Details of specific use :

Your data

Company name :
 Your name :
 e-mail :
 Phone : Postal code and country :



Headquarters and factory

21 rue Sadi Carnot
94880 Noiseau (France)
e-mail : contact@cable-equipements.fr

Commercial office

Worringer Straße 30
D-50668 Köln (Deutschland)
e-mail : kontakt@cable-equipements.com

Tel. : (+33) 01 45 90 14 14
www.cable-equipements.com